



PC-TOUCH



GT800

Features

- Graphical touch screen display 5,7" - 17"
- 400 MHz - 1 GHz CPU
- Application stored on either SD card or HDD
- User-defined design option (GT800)
- OS Windows
- Several applications possibility (attendance, meal ordering)
- Integrated ID reader
- Many ports for peripherals connection
- Wall-mounting
- ON-LINE operation

Modern terminals, based on PC architecture and equipped with card reader ■ Touchscreen display provides broad range of possibilities in user interface creation and simplifies control to touching the function icon on the screen ■ Yet another advantage of these devices is the possibility to run several applications and switch between them ■ The attendance and catering systems are typical implementations, as these need to monitor attendance and order meals using one device for maximum user comfort.

Touchscreen terminals will find their use also in Smart House Systems - as central controlling and visualizing unit.

| Product Code | Description |
|--------------|--|
| GT800 | Attendance PC Terminal with inside contactless reader, ETHERNET CPU 300/400 MHz, display 5,7", Flash or SD memory for application |
| GT810 | Catering PC Terminal with inside contactless reader, ETHERNET CPU 300/400 MHz, display 5,7", Flash or SD memory for application |
| GT830 | Attendance and Catering PC Terminal, combination GT800+GT810 |
| PC-TOUCH | Compact PC Touch Terminal with card reader, wall-mounting holder Display 15"-17", CPU/RAM according to actual offer, HDD Used in the catering systems for food order and access to INTRNET, as a cashier terminal with various possibilities of POS equipment connection |

PC-TOUCH terminal is supplied with installed operation system only. Other needed applications are necessary to be ordered separately.



TECHNICAL SPECIFICATION

| Type designation | GT800 |
|-------------------------|---|
| Power Supply | DC 10 - 30V (typ. 12V) |
| Input current | Max 790 mA (@12V DC) Max 350 mA (@12V DC) |
| Size (h x w x d) | 265 x 146 x 47 mm |
| Casing | IP 40 |
| Weight | 1600 g |
| Working temperature | 0°C to +50°C |
| Storage temperature | -20°C to +50°C |
| Outputs | 2x transfer relay , max. 30V 2A 4x open connector 30V/0,5A |
| Inputs | 4x galvanically isolated 4-30V DC |
| Tamper | YES |
| Communication interface | LAN, USB, RS232, RS485, CAN extension - WLAN, BT, READER RFID (BIOMETRIC, WIEGAND) |
| Parameters | CPU 300/400 MHz, TFT VGA DISPLAY 5,7", TOUCH PANEL, 32 MB FLASH, 32 MB SDRAM, WINDOWS CE S.O, SLOT PRO KARTY SD/PCMCIA |
| Montage | implementation on the wall / lifting |

