



RD3



RD3B



RD3F

Cards, chips and fingerprints table readers for connection to computer.

They are used to enter ID data into database as well as help with everyday tasks such as fast searching. Issuing visitor's cards or key cards at the front desks in hotel systems is yet another use for these readers. In catering systems, they can be used to carry out payments for taken meals.

They use the USB or COM port for computer connection.

Product Code	Description
RD3	Contact Table Reader, USB connection
RD3B	Contactless Table Reader, USB connection
RD2	Contact Table Reader, RS232, external power needed
RD2B	Contactless Table Reader, RS232, external power needed
RD3F	Biometric Table Reader, USB connection

It is also possible to order SW drive, which allows scanning ID media wherever necessary for further processing.

## TECHNICAL SPECIFICATION

Type designation	RD3	RD3B	RD3F
Power Supply	USB (5V)	USB (5V)	USB (5V)
Input current	Max 40 mA	Max 150 mA	160 mA
Size (h x w x d)	92 x 58 x 25 mm	92 x 58 x 25 mm	54 x 34 x 14 mm
Cable length	1800 mm	1800 mm	6700 mm
Casing	IP 40	IP 40	IP 40
Weight	109 g	100 g	20 g without cable
Working temperature	-25 °C to +50 °C	-20 °C to +50 °C	-10 °C to +50 °C
Storage temperature	-40 °C to +50 °C	-40 °C to +50 °C	-20 °C to +70 °C

