

Features

- Capacity of up to 1,000 users
- Possibility to connect 2 readers
- Various identification types (chip, card, fingerprint)
- Inputs for door contacts
- Communication via ETHERNET
- Safety case
- Tamper contact against case opening
- Event log
- 3x universal relay
- No need for special SW



Compact electronic system to control entrance into condos and other common spaces ■ Suitable for houses, offices, driveways or lifts as well ■ It is possible to connect up to 2 readers for independent control of two entrances (AS3003) ■ Two relays control doorlocks, the third one is for lighting control or for alarm to signal forceful breach, for example ■ Integrated web server to allow easy access to card rights assignment and configuration ■ Also programmable using master card or chip without the need of computer connection.

Can be operated with either of two power supply options – 230 V with internal accumulator backup, or 11-20V AC/DC for easy integration into existing doorbell systems

Product Code	Description
AS3001	One Door Set, contact identification, external power supply necessary, IP56 casing
AS3002	One Door Set, contact identification, including backed-up power supply
AS3003	Two Doors Control Unit, including backed-up power supply, without reader Up to 2 readers EDK2 or 1 any WIEGNAD reader can be connected



Wiring for connection to PC is included in the delivery. Backed-up power supply for AS3002, AS3003 is sold separately.